

Turning Inserts

WNMG PM for Medium Machining




Coated Grades - CVD

YBM251

ANSI	ISO	L (Inch)	ØI.C. (Inch)	S (Inch)	Ød (Inch)	r (Inch)	Code
WNMG-332-PM	WNMG-060408-PM	0.256	0.375	0.187	0.150	0.031	575920
WNMG-431-PM	WNMG-080404-PM	0.343	0.500	0.187	0.203	0.016	575964
WNMG-432-PM	WNMG-080408-PM	0.343	0.500	0.187	0.203	0.031	575725
WNMG-433-PM	WNMG-080412-PM	0.343	0.500	0.187	0.203	0.047	575739

To be used with holders: PWLNR/L; MWLNR/L





EXAMPLE: MWLNR



WNMA No Chipbreaker



NEGATIVE 80° TRIGON



WNMA

Coated Grades - CVD

YBD102

ANSI	ISO	L (Inch)	ØI.C. (Inch)	S (Inch)	Ød (Inch)	r (Inch)	Code
WNMA-332	WNMA-060408	0.256	0.375	0.187	0.150	0.031	575860
WNMA-432	WNMA-080408	0.343	0.500	0.187	0.203	0.031	575866


YBD151

ANSI	ISO	L (Inch)	ØI.C. (Inch)	S (Inch)	Ød (Inch)	r (Inch)	Code
WNMA-332	WNMA-060408	0.256	0.375	0.187	0.150	0.031	575862
WNMA-432	WNMA-080408	0.343	0.500	0.187	0.203	0.031	575868

YBD152

ANSI	ISO	L (Inch)	ØI.C. (Inch)	S (Inch)	Ød (Inch)	r (Inch)	Code
WNMA-332	WNMA-060408	0.256	0.375	0.187	0.150	0.031	575864
WNMA-432	WNMA-080408	0.343	0.500	0.187	0.203	0.031	575870

To be used with holders: PWLNR/L; MWLNR/L



EXAMPLE: MWLNR