

Electronic Depth Micrometer



- Resolution: 0.00005"/0.001mm
- Coolant proof, IP54 Ingress protection level
- Flat tips
- Base length: 4"/101.5mm
- Buttons: power on/off, inch/mm conversion, absolute and incremental measurement, set data, data output
- Battery SR44
- With battery cover wrench
- Auto power off
- Data output via RS232 (RS232 cable included, SPC connection cable optional)
- Supplied in fitted storage case



Range (Inch/mm)	Code
0-6/0-150	281945
0-12/0-300	281947

Electronic Blade Micrometers



- Resolution: 0.00005"/0.001mm
- The anvil and spindle have blade tips to measure the groove diameter of shafts and keyways
- Blade tip: 0.03 x 0.235 x 0.256" (0.75 x 6 x 6.5mm)
- Buttons: power on/off, inch/mm conversion, absolute and incremental measurement, data set
- Data output via RS232 (RS232 cable included, SPC connection cable optional)
- Auto power off
- SR44 battery
- Non-rotating spindle
- With battery cover wrench
- Micrometers over 1"/25mm are supplied with a setting standard
- Supplied in fitted storage case



Range (Inch/mm)	Code
0-1/0-25	281327
1-2/25-50	281328
2-3/50-75	281329

Outside Micrometers with Counter



- DIN863
- Ratchet stop, carbide tips and zero adjusting wrench
- Micrometers over 1"/25mm are supplied with a setting standard
- Supplied in fitted storage case



Inch

Range (Inch)	Counter Readout (Inch)	Thimble Graduation (Inch)	Code
0-1	0.001	0.0001	280933
1-2	0.001	0.0001	280934
2-3	0.001	0.0001	280935
3-4	0.001	0.0001	280936
4-5	0.001	0.0001	280937
5-6	0.001	0.0001	280938

Metric

Range (mm)	Counter Readout (mm)	Thimble Graduation (mm)	Code	Range (mm)	Counter Readout (mm)	Thimble Graduation (mm)	Code
0-25	0.01	0.01	280918	75-100	0.01	0.01	280921
25-50	0.01	0.01	280919	100-125	0.01	0.01	280922
50-75	0.01	0.01	280920	125-150	0.01	0.01	280923