

## Live Centers

### Super Quad Extra Heavy-Duty

- Designed for very large, heavy parts — up to 12,000 lbs
- $\pm 0.00005$ " total indicator runout guaranteed
- Three huge angular contact bearings and a beefy needle roller bearing combine to form a very strong, rigid assembly
- Large, sturdy point and thick-walled head ensure minimal deflection under load
- Body and point are hardened for strength and durability



Morse Taper	B (Inch)	E (Inch)	F (Inch)	G (Inch)	Maximum RPM	Weight (lbs)	Thrust Load	Code
4	3-11/16	3-5/16	1-3/4	1-5/8	4000	3325	4800	826265
5	4-15/16	4-5/16	2-7/16	2-3/8	3000	10650	13220	826266
6	4-15/16	4-5/16	2-7/16	2-3/8	3000	10650	13220	826267
6	6-15/16	5-11/16	3-7/32	3-1/8	2500	12130	25920	826268

### Heavy-Duty Spindle Type – Standard Point & CNC Point

- An excellent heavy-duty live center designed to handle most turning applications
- $\pm 0.00005$ " total indicator runout guaranteed
- Heavy-duty precision bearings provide exceptional thrust and radial load capacities
- The substantial point extends into the shank where it is supported by a large needle bearing for increased strength and rigidity
- Body and point are hardened for strength and durability
- On the CNC model, the extended point provides great tool clearance

#### Standard Point



Morse Taper	B (Inch)	E (Inch)	F (Inch)	G (Inch)	Maximum RPM	Weight (lbs)	Thrust Load	Code
2	1-3/4	1-7/16	1-1/32	7/8	6000	725	2360	826270
3	2-3/8	1-3/4	1-1/4	1	5000	970	3900	826271
4	2-11/16	1-31/32	1-1/2	1-1/4	4500	1720	4050	826272
5	3-1/2	2-13/16	1-7/8	1-1/2	3500	3260	5700	826273
6	4	3-5/32	2-5/16	2	3500	4080	6000	826274