

## Universal Lathe Chucks

### Semi-Steel Body – 3-Jaw Direct Mount Chucks

2 Pc. Jaws




### Camlock D1 Chucks – Series 3245

Chuck Diameter (Inch)	Mount	d Hole Diameter (Inch)	B (Inch)	G (Inch)	C (Inch)	H (Inch)	h (Inch)	Code
5.00	D1-4	1.26	3.25	2.50	0.51	2.76	1.57	355023
6.25	D1-3	1.65	2.78	2.12	0.51	3.21	1.69	355024
6.25	D1-4	1.65	3.25	2.50	0.51	3.21	1.69	355025
8.00	D1-3	2.03	2.78	2.12	0.51	3.58	1.77	355026
8.00	D1-4	2.17	3.25	2.50	0.51	3.58	1.77	355027
8.00	D1-5	2.17	4.13	3.25	0.56	3.58	1.77	355028
8.00	D1-6	2.17	5.25	4.19	0.56	3.58	1.77	355029
10.00	D1-5	2.99	4.13	3.25	0.56	4.07	2.09	355030
10.00	D1-6	2.99	5.25	4.19	0.63	4.07	2.09	355031
10.00	D1-8	2.99	6.75	5.50	0.71	4.07	2.09	355032
12.50	D1-6	4.06	5.25	4.19	0.63	4.63	2.24	355033
12.50	D1-8	4.06	6.75	5.50	0.71	4.63	2.24	355034
12.50	D1-11	4.06	9.25	7.75	0.79	5.51	2.24	355035
15.75	D1-6	4.06	5.25	4.19	0.63	5.06	2.64	355036
15.75	D1-8	5.35	6.75	5.50	0.71	5.06	2.64	355037
15.75	D1-11	5.35	9.25	7.75	0.79	5.06	2.64	355038
20.00	D1-8	5.35	6.75	5.50	0.71	5.75	3.15	355039
20.00	D1-11	7.60	9.25	7.75	0.79	5.75	3.15	355040
25.00	D1-11	7.60	9.25	7.75	0.79	6.50	3.42	355041

### Semi-Steel Body – 3-Jaw Self-Centering Chucks

#### Threaded Chucks – Series 3285



Chuck Diameter (Inch)	Hole Diameter (Inch)	Thread	Approximate Weight (lbs)	Code
5	1.2598	1 - 10	10.0	355055
5	1.2598	1-1/2 - 8	10.0	355056
6	1.6535	1-1/2 - 8	18.1	355057
6	1.6535	2-1/4 - 8	18.1	355058
8	2.1654	1-1/2 - 8	33.7	355059
8	2.1654	2-1/4 - 8	33.7	355060
8	2.1654	2-3/8 - 6	33.7	355061
10	2.9925	2-1/4 - 8	55.3	355062
12	4.0551	2-3/8 - 6	90.4	355063
12	4.0551	<b>2-3/4 - 8</b>	90.4	355064

*\*Updated since print version*