

## Digimatic Height Gages

Mitutoyo

### Standard Type

- Resolution: 0.0005"/0.01mm (0.0002"/0.005mm switchable)
- Easy-to-use standard type
- Carbide-tipped scriber is provided
- Double-column structure ensures high measuring accuracy
- Coarse/fine feed switching
- Switchable resolution
- Two preset reference heights

### Multi-Function Type with SPC Data Output

- Resolution: 0.0005"/0.01mm (0.0002"/0.005mm switchable)
- Highly versatile multi-function type
- Carbide-tipped long scriber is provided
- Rigid construction ensures repeatable measurement
- Switchable resolution
- Coarse/fine feed switching
- SPC data output
- Two preset reference heights

Bi-directional touch-signal probe is an optional accessory. It can quickly and accurately measure steps, and inside and outside widths.



### Standard

Range (Inch/mm)	Accuracy (Inch)	Weight (kg)	Code
0-12/0-300	±001	4.7	192-630-10
0-18/0-450	±002	7.5	192-631-10

### Multi-Function

Range (Inch/mm)	Accuracy (Inch)	Weight (kg)	Code
0-12/0-300	±001	5.7	192-670-10
0-18/0-450	±0015	7.5	192-671-10
0-24/0-600	±0015	8.3	192-672-10